



SKF PFT 40 RM Unidades de rolamento

Bearing No. PFT 40 RM

Bore Diameter	40 mm
Width	36 mm
d	40 mm
Da	91 mm
A1	3,5 mm
B	36 mm
G	12 mm
H	148 mm
H1	– mm
J	119 mm
L	104 mm
N	13,5 mm
T	28,8 mm
A2	10 mm
Weight	0,78 Kg
Basic dynamic load rating (C)	30,7 kN
Basic static load rating (C0)	19 kN
Housing material	Pressed steel
Da min.	87 mm
A ₁	3.5 mm
A ₂	10 mm
B ₄	7 mm
s ₁	25.3 mm
Basic dynamic load rating C	30.7 kN
Basic static load rating C ₀	19 kN
Fatigue load limit P _u	0.8 kN

PFT 40 RM Bearing 2D drawings and 3D CAD models



DODGE CONSOLIDATED BEARING CO., LTD.

Limiting speed	4800 r/min
Mass bearing unit	0.79 kg
Thread grub screw G_2	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N · m
Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in